

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

MAKE:	MODEL:	CATEGORY										
ENGINE No.	VIN:											

ADR 8/01 – SAFETY GLAZING MATERIAL

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
5.3	Is transparent material other than glass used in the vehicle? If YES, note the location and markings. Location..... Marking.....	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
6.1	All glazing suitably marked?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
5.4	Windscreen glass marked as being laminated?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR 14/02 – REAR VISION MIRROR

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
14.5	(1) Two rear vision mirrors, symmetrically placed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Both flat (F) or convex (C)?	<input type="checkbox"/>	
14.7	If 'E' marked, R46 Approval No or R81 Approval No.	#	

ADR 18/03 – INSTRUMENTATION (LC, LD ONLY From 01-July-06 for ALL NEW MODELS)

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
5.1	Vehicle speed indicated in km/h only? If NO Is the mp/h scale the secondary scale?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.5.1	Speedometer located within direct field of view of the driver and clearly legible both day and night?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.5.1.1	Speed values indicated in intervals not exceeding 20km/h (when the highest value on the display is less than 200km/h), or 30km/h (when the highest value is more than 200km/h). ? Please circle. Graduations at least in 1, 2, 5 or 10km/h increments?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR 19/01 and 19/02- INSTALLATION OF LIGHTING & LIGHT SIGNALLING DEVICES

(NOT APPLICABLE FOR LB AND LEM CATEGORY CERTIFIED TO ADR 67/00)

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
A.5.5.1	GENERAL Are all lamps constituting a pair symmetrical?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.5.9	No red light visible from the front and no white light (except reversing light) visible from the rear of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT

FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM

A.5.10	Are the front position lamps (if fitted), rear position lamps and the rear registration plate lamp switched on and off simultaneously?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>						
A.5.11	Impossible to switch on the main-beam, the dipped-beam and the front and rear fog lamps (if fitted) without switching on the lamps referred to in clause A.5.10?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>						
(1) If any item in column 1 is 'E' Marked note marking in Column 2. (2) Audit at least 2 items for each of Columns 3 to 9 inclusive. Circle non-compliances, otherwise tick. (3) Indicate compliance status for table at end in space provided.								
FEATURES								
(1) FEATURE	(2) If 'E' Marked Approval No.	Height (#)		(5) APART	(6) EDGE	(7) G	(8) C	(9) R
		(3) MAX	(4) MIN	(#)	(#)	(*)	(*)	(*)
Main beam (*)				<200	Dipped beam	Dipped		Dipped
Dipped beam (*)		1200	500	<200	(a) <400	Main		Main
Direction Indicator Front (*)		1200	350	>240	(a) <400			
Direction Indicator Rear (*)		1200	350	>180	(b) <400			
Stop lamp (*)		1200	250	(b) >400		R/p os	R/po s	R/pos

Notes:.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 19/01 and 19/02- INSTALLATION OF LIGHTING & LIGHT SIGNALLING DEVICES Cont.

FEATURES								
(1) FEATURE	(2) If 'E' Marked Approval No.	Height (#)		(5) APART	(6) EDGE	(7) G	(8) C	(9) R
		(3) MAX	(4) MIN	(#)	(#)	(*)	(*)	(*)
Rr. Regisn. Plate lamp (*)						R/pos	R/pos	
Fr. Position lamp (*)		1200	350		<400 (a) <150 (c)	Dipped	Dipped	Dipped
Rr. position lamp (*)		1500	250	>400 (b)	<400 (b) <150 (c)	Stop	Stop	Stop
Reflex reflector Rear (*)		900	250	>400 (b)	<400 (b, c)	R/pos	R/pos	
Reflex reflector Side (*)		900	300					
Front fog lamp (+)		<Dipped Beam	250	<250 from c/l				
Rear fog lamp (+)		900	250	>100 form stop				
Parking lamp (For LB, LD, only) (+)		1200	350					
Reversing lamp (For LB, LD, if reverse gear fitted)		1200	250			R/pos	R/pos	

Notes:.....
.....
.....

IR-3

SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT

FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM

ADR 19/01 and 19/02- INSTALLATION OF LIGHTING & LIGHT SIGNALLING DEVICES Cont.

(*) = Mandatory (+) = If fitted; All dimension in mm. (#) = HEIGHT - To highest (Max) and lowest (Min) points on illuminating surface. Apart – Distance between innermost edges of illuminating surface. EDGE – Maximum distance from outer edge of vehicle to illuminating surface.		a = For LB2 vehicles only b = For LB1 vehicles only c = For LD vehicles Column (7) to (9) indicates specific lamps which may be grouped (G), combined (C) or reciprocally incorporated (R).	COMPLIANCE Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	SSR No.
CLAUSE No.	FEATURE	COMPLIANCE	SSR No.	
A.6.1	DRIVING(MAIN) BEAM HEADLAMPS	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.1.3.1	Geometric centre located in longitudinal median plane? If NO Is its centre of reference symmetrical in relation to another driving/passing/front position lamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.1.3.3	Is the distance between the edges of the illuminating surface of any independent driving lamp and the edge of that of the passing lamp not more than 200mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.1.3.4	If 2 driving lamps fitted is the distance between the illuminating surfaces not more than 200mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.1.8	Non-flashing ("Circuit-Closed")-tell-tail blue and operating?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.2	PASSING BEAM (DIPPED) – HEADLAMPS	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.2.3.1.2	Centre of lamp in longitudinal median plane? If NO Is its centre of reference symmetrical in relation to another driving/passing/front position lamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.2.3.4	If 2 passing lamps fitted is the distance between the illuminating surfaces not more than 200mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.2.7	Are all driving beams switched 'OFF' when changing from driving to passing beam?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.2.8	If fitted, is operational tell-tale colour green and non-flashing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.3	DIRECTION INDICATOR LAMP	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.3.3.1	(1) Front indicators at least 240mm between illuminating surfaces? (2) Front indicators outside vertical planes tangential to outside of headlamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.3.3.1	(1) Distance between the illuminating surface of the indicator and passing beam headlamp at least 75mm? If NO Note distance between illuminating surfaces.....mm	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.3.3.1	Illuminating surfaces of rear indicators at least 180mm apart?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.3.3.3	Rear indicators within 300 mm of rear end of vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
A.6.3.8	Independent switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
	Lamps on one side operated by one control	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		

Notes:.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 19/01 and 19/02- INSTALLATION OF LIGHTING & LIGHT SIGNALLING DEVICES Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
A.6.3.9	Operating Green or Yellow Tell-tale fitted? If no	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Is an audible operating tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If any direction indicator lamp defective, does tell-tale show, (A) - Marked frequency change, (B) - Continuously on, or (C) – Continuously off (Indicate A, B, C,)?,	<input type="checkbox"/>	
A.6.3.10.1	Flash rate 60 –120 times per minute?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.2	Flash in phase on same side?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.3	Light up within 1 sec, and extinguishes within 1.5 sec?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.3.10.4	In the event of a failure, other than a short circuit, the other direction indicator on the same side continues to flash or remain alight?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.4	STOP LAMP	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.4.6	Lighted on any front or rear service brake application?		
A.6.5	REAR – REGISTRATION PLATE ILLUMINATING DEVICE	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.5.2	Illuminates registration plate area?		
A.6.6	FRONT POSITION LAMP (IF FITTED, MANDATORY FOR 19/02)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.6.1	One or Two lamps fitted? Please circle number of lamps.		
A.6.6.6	Green ‘Circuit-closed’ tell-tale fitted? If NO	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Instrument lights as tell-tale?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.7	REAR POSITION LAMP	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.7.1	One or Two lamps fitted? Please circle number of lamps		
A.6.7.6	If “Circuit-closed” tell-tale fitted, is it the same as front position lamp tell-tail?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.8	REAR REFLEX REFLECTOR, NON-TRIANGULAR	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.8	One or Two reflectors fitted? Please circle number of reflectors fitted.		
A.6.9	VEHICLE – HAZARD WARNING SIGNAL (OPTIONAL)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.9.2	Separate control operates all direction Indicator lamps?		
A.6.9.3	(1) Circuit closed tell-tale provided?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) If single tell-tale, signal flashing red?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) If separate , is tell-tail the same as direction indicators?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.9.4	Capable of activation when the device which controls the starting and stopping of the engine is in such a position that operating the engine is impossible?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.10	FRONT FOG LAMP (OPTIONAL)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.10.1	Are ONE or TWO lamps fitted? Please circle		
A.6.10.3.1	If fitted, is it on the median longitudinal plane or is the illuminating edge within 250 mm of it?		
A.6.10.9	Possible to operate the fog lamp independently of the driving-beam and the passing-beam head lamp(s)?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 19/01 and 19/02- INSTALLATION OF LIGHTING & LIGHT SIGNALLING DEVICES Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
A.6.10.7	If fitted, tell-tale non-flashing green?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.11	REAR FOG LAMP (OPTIONAL)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.11.1	Are ONE or TWO lamps fitted? Please circle		
A.6.11.3.3	Distance from edge of stop lamp not less than 100 mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.11.6	(1) Can only light up when either the main-beam or the dipped-beam or the front fog lamp is switched on?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Rear fog lamp switch independent of the front fog lamp switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) With the rear fog lamps switched 'ON' does switching 'OFF' the position lamp, extinguish the it and does it remain 'OFF' until deliberately switched 'ON' again?		
A.6.11.7	Is an amber "Circuit-closed" non-flashing tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.12	SIDE REFLEX REFLECTOR, NON-TRIANGLE (OPTIONAL FOR VEHICLES CERTIFIED TO ECE R53/00)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.12.1	Are ONE or TWO side reflectors fitted, per side? Please circle. If 2 side reflectors fitted, is front reflector AMBER? Is rear reflector AMBER or RED? Please circle.	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
A.6.12.3.3	Positioned such that the reflector(s) are not be masked by the driver's or passenger's clothes?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1	PARKING LAMP (OPTIONAL)		
7.1.2	Arrangement, ONE or TWO at FRONT, ONE or TWO at REAR, Please circle.	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.3	ON or to RIGHT or on EITHER side of the median longitudinal plane?		
7.1.6	(1) Independent switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Possible to operate with the ignition in the 'OFF' position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.7	If tell-tale fitted, is it impossible to confuse it with that for the front and rear position lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.2	REVERSING LAMP (ONLY IF REVERSE GEAR FITTED)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.2.6	Is the lamp always lit when reversing gear engaged?, and		
	(1) The device controlling starting and stopping the engine is in a position where the engine can operate? (2) The engine is running?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.4	FRONT REFLEX REFLECTOR NON-TRIANGULAR (OPTIONAL FOR LA, LC AND LD)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.4.1	Are ONE or TWO side reflectors fitted? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.4.3	(1) If only one reflector fitted, the centre of reference is on the vehicle medium longitudinal plane?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) If two reflectors fitted, is the illuminating surface not more than 400mm from the extreme outer edge of the side car.		

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 19/01 and 19/02- INSTALLATION OF LIGHTING & LIGHT SIGNALLING DEVICES Cont.

CLAUSE No	FEATURE	COMPLIANCE	SSR No.
8.9	CONSPICUITY LAMP (MANDATORY FOR VEHICLES CERTIFIED TO 19/01) Are TWO conspicuity lamps fitted, or is conspicuity lamp incorporated in passing beam headlamp? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
8.9.9.1	Conspicuity lamp is lighted with the engine running?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR 23/02 - PASSENGER CAR TYRES (IF FITTED)

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
SE verification	For one tyre fitted, identify: (If tyre size different front and rear, complete for 1 Fr & 1 Rr tyre) (1) Manufacturer or trade mark Fr..... Rr..... (2) Tyre size, speed category and carcass construction symbols Fr..... Rr..... (3) ECE Approval. Fr..... Rr.....	#	
6.3.1	At least 6 tread traverse rows of wear indicators?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
3.1	Each tyre labelled on both sides, (in the case of symmetrical tyres)?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR 33/00 – BRAKE SYSTEMS FOR MOTORCYCLE AND MOPEDS (ALL L-CATEGORIES)

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
33.2.1.1	Split (S) or independent (I)? Indicate S or I.	<input type="checkbox"/>	
33.2.1.4	Lining visible either directly or indirectly?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.1.6	Brake controls readily accessible?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.1.7	Adequate provision made for adjustment?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.5.1	Separate reservoir compartment for each sub-system?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.5.3	Labelling satisfactory and located on or near brake fluid reservoir cap?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.3.0	If split service brake system, failure indicator lamp: (1) Fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.3.2	(2) Activation check satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.3.5	(3) Labelling satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 33/00 – BRAKE SYSTEMS FOR MOTORCYCLE AND MOPEDS (ALL L-CATEGORIES) Cont.

33.2.4	If single brake power unit, an audible device provided?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.2.2	Parking brake provided? (LB, LD & LE only)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
33.6	If E marked, R78 Approval No	#	

ADR 42/04 - GENERAL SAFETY REQUIREMENTS

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
6	DIESEL ENGINES Is device fitted to prevent inadvertent starting of engine?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1	STEERING SYSTEM Steering wheel located centrally or to the right?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.2	Is effective steering of the vehicle maintained due to failure of any non-mechanical component of the steering system? (For non-mechanical steering only)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.3	For vehicles with 'Full-Power Steering Equipment' is a steering failure/defect visual warning signal provided to the driver?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9.1.1	ELECTRICAL WIRING Supported at not more than 600 mm intervals?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9.1.2/3/4	Properly insulated, located and protected from chafing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
11.1.1/2/3	EXTERNAL OR INTERNAL PROTRUSIONS Devoid of external or internal projections or sharp or pointed fittings?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
12.1	FIELD OF VIEW Driver's view on either side and in all directions in front of the vehicle unobstructed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
14.3.2	WHEEL GUARDS (MUDGUARDS) Are wheels fitted with guards, or permanent structure, that cover at least the 'Section Width' of the tyre, and designed as to protect other road users against thrown-up stones, mud, ice, snow and water?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
14.3.3.1	Do Rear wheel guards covers the wheel from a point vertically above the foremost part of the wheel to an arc rearwards up to a line through the centre at or less than 45 degree to horizontal?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
14.3.3.2	Unless bodywork provides required protection, do front wheel guards extend over rear quarter of wheel?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
15	BRAKE TUBING AND BRAKE HOSES For any one brake hose (if fitted) identify (1) Location Markings.....	#	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 42/04 - GENERAL SAFETY REQUIREMENTS Cont.

15	Brake tubing and hoses fitted to prevent chafing, kinking or other mechanical damage?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
20.2	WARNING DEVICE AUDIBLE Fitted with at least one horn with constant amplitude and frequency characteristics?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
25.3.1	TYRE AND RIM SELECTION All tyres fitted to an 'Axle' are the same type of 'Carcass' construction?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR 43/04 – VEHICLE CONFIGURATION & DIMENSIONS

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
6.5.2.1	LA & LC overall width does not exceed 1000mm (not including mirrors or lamps)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
6.5.2.2	3 Wheel vehicles overall width does not exceed 1850mm (not including mirrors or lamps)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR 57/00 - SPECIAL REQUIREMENTS FOR L-GROUP VEHICLES (LA, LC & LD only)

CLAUSE No.	FEATURE		COMPLIANCE	SSR No.	
57.2.1	SIDE-CARS Side-car securely attached to left hand side?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2	STEERING GEAR		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.1	Handlebars extend not less than 250 mm and not more than 450 mm on each side of centre line?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.2	Height of lowest part of handgrip above lowest part of upper surface of driver's seat <380mm?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.3	Steering gear designed to prevent over locking?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.4	Horizontal distance from mid-point between head stems bearing to centre of front wheel <550 mm?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.2.5	Handlebars symmetrical and located centrally?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>		
57.2.3	OPERATION AND LOCATION OF CONTROLS (Circle non-compliance)				
	CONTROL	LOCATION	OPERATION	COMPLIANCE	SSR No.
	Manual clutch (*)	Left HB? (#)	Squeeze to disengage?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Gear change (Opt)	Left Foot?	Up from first gear to select others?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Head Lamp (**)	Left HB?	Up – main beam, down – dipped and 'Off-guard' provided if combined with on-off switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Horn	Left HB?	Push to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Direction Indicator	Either HB?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 57/00 - SPECIAL REQUIREMENTS FOR L-GROUP VEHICLES (LA, LC & LD only) Cont.

CONTROL	LOCATION	OPERATION	COMPLIANCE	SSR No.
Ignition (Opt)		Anti-clockwise to 'OFF' from other positions?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Manual only fuel shut-off (Opt)		Off-forward, On-downwards, Reserve (if provided) – On-upwards? Or As per FMVSS 123? (Rotate to operate). "On" and "Off" separated by 90 degrees of rotation. "Off and "Reserve" (if provided) separated by 90 degrees of rotation? Order "On"- "Off"- "Reserve"	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Twist grip throttle	Right HB?	Self-closing in clockwise direction to idle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Supplemental engine stop	Right HB?	Thumb operated	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Front Brake	Right HB?	Squeeze to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Rear Brakes For LC	Right Foot	Depress to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
If Auto trans	R.Foot/L.HB?	Squeeze to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
For LA, LB	Left HB?	Squeeze to activate?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
(*) – Hand lever or combined with gear change. (**) – Only dipped beam permitted for LA category vehicles. (#) – HB = Handle Bar.				
CLAUSE No.	FEATURE		COMPLIANCE	SSR No.
57.2.3.1.2	OPERATION REQUIREMENTS Without removal of the operator's right hand from the throttle, are the following operations possible? (1) Hand lever control of front brake		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Turn signal control (if on right handlebar)?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) supplemental engine stop?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
57.2.3.1.3	Without removal of the operator's left hand from the handgrip, are the following operations possible? (1) Hand lever control of clutch and push horn button?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Turn signal control (if on left handlebar)?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Headlamp beam control (except for LA)?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 57/00 - SPECIAL REQUIREMENTS FOR L-GROUP VEHICLES (LA, LC & LD only) Cont.

Clause No. 57.2.3.3	CONTROL AND VISUAL INDICATOR DISPLAY IDENTIFICATION If an item of equipment listed below is provided, is it and its control positions identified at least as specified (*).			
Item	Identification & Visibility	Position Identification *	COMPLIANCE	SSR No.
Ignition switch #		OFF?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Supplemental engine stop	Engine stop?	OFF, run?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Manual choke #	Choke?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Electric starter		Start?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Headlamp beam control	Lights?	Hi, Lo?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Horn	Horn?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Direction indicator	Turn?	L, R?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Main beam indicator	Main Beam?	Blue Indicator.	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Tachometer	R/min, rpm, RPM, or min-1		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Fuel tank shut off Control #	Fuel?	Off, On, Res?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Neutral Indicator	Neutral?	Green Indicator.	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Speedometer	km/h only?	Major graduations at 10km/h intervals?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
# - Visibility to seated driver not required.				
* - The equivalent ISO symbol is an acceptable alternative.				
CLAUSE No.	FEATURE		COMPLIANCE	SSR No.
57.2.4	TRANSMISSION REQUIREMENTS (IF TRANSMISSION MANUAL) Is disengagement possible at any engine speed?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
57.2.5	ELECTRICAL GENERATOR AND BATTERY Fitted with a battery or generator? (B or G)?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
57.2.6	FOOTREST Foot rest fitted for each seating position?		Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT

FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM

ADR 57/00 - SPECIAL REQUIREMENTS FOR L-GROUP VEHICLES (LA, LC & LD only) Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
57.2.7	STANDS (FOR LA AND LC VEHICLES ONLY) Stand holds vehicle upright and device keeps stand off road?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
57.2.8	CHAIN GUARDS (IF CHAIN DRIVEN) Front sprocket and upper free run of chain covered to >300 mm rear of rear most footrest, or to a point vertically above the centre of the rear drive sprocket?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
57.3	If E marked, R60 Approval No.....	#	

ADR 61/02 - VEHICLE MARKING

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
5	VEHICLE IDENTIFICATION NUMBER	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
5.1	(1) Is the VIN clearly visible on an integral part of the vehicle and not easily removed?		
	(2).If VIN is directly marked on an integral part of the vehicle, is the minimum height at least 4mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) If VIN is on a separate plate, which in turn is permanently affixed to an integral part of the vehicle, is the minimum height at least 4mm?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
6	COMPLIANCE PLATE	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
6.1	Is an approved Compliance Plate fitted in the location specified on the RVD form		
6.1	If YES, is it satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
Circ 0-3-8	FOR ADHESIVE COMPLIANCE PLATE LABELS		
	(1) Is a VIN bar code included on the label?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Is the label resistant to counterfeiting?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Is a manufacturer's Logo or other unique identifier included on the label?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7	ENGINE NUMBER	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1	Is the engine number permanently stamped, cast, laser engraved, or a combination of these on the main component of the engine?		
7.1.1			
7.1.2	Can a legible engine number be readily seen when the engine is installed	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
7.1.3	in the vehicle? If 'No' is one of the following met?		
	1. Are only simple hand tools required to remove any vehicle components?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Or		
	2. Is a supplementary label placed in a conspicuous position in the engine compartment?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Is the label adequately durable for its environment, and not removable		
	other than by its destruction?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 61/02 - VEHICLE MARKING Cont.

	Is the engine number satisfactorily located as per typical number on the RVD form?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9 .9.1.2.1	REGISTRATION PLATES Is there provision to mount a rear number plate no lower than 300 mm from the ground??	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
9.2.2	LABEL HOLDER Is a holder for the registration label present and in a conspicuous position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY)

(1) If any item in column 1 is 'E' Marked note marking in Column 2. (2) Audit at least 2 items for each of Columns 3 to 9 inclusive. Circle non-compliances, otherwise tick. (3) Indicate compliance status for table at end in space provided.								
FEATURES								
(1) FEATURE (CLAUSE No.)	(2) If 'E' Marked Approval No.	Height (#)		(5) APART (#)	(6) EDGE (#)	(7) G (*)	(8) C (*)	(9) R (*)
		(3) MAX	(4) MIN					
Main beam (CI 67.4.1) (*)					(*) Dipped beam	Dip		Dip
Dipped beam (CI 67.4.2) (*)		1200	(*) 500		400	Main		Main
Front fog lamp (CI 67.4.10) (+)		<Dip. beam	250		400	%f		Main Swiv
Reversing lamp (CI 67.4.14) (*)		1200	250			%r		
Direction indicato Front (CI 67.4.3) (*)		1200	350	300 ≥ 100 MAIN OR DIP	400	%f		Park
Direction indicator Rear (CI 67.4.3) (*)		1200	350	240	400	%r		Park
Direction indicator side (CI 67.4.3) (*)								

Notes:.....

IR-3

SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT

FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY) Cont.

FEATURES								
(1) FEATURE (CLAUSE No.)	(2) If 'E' Marked Approval No.	Height (#)		(5) APART	(6) EDGE	(7) G	(8) C	(9) R
		(3) MAX	(4) MIN	(#)	(#)	(*)	(*)	(*)
Stop lamp (Cl 67.4.4) (*)		1200	350	600/400 (67.4.4.3.1.2)		%r		R/Posn Park
Rr. Regisn. Plate lamp (Cl 67.4.5) (*)						%r	%r	%r
Fr. Position (side) lamp (Cl 67.4.6) (*)		1500	350	Symmetrical	400	%f		%f
Rr. position (side) lamp (tail lamp) (Cl 67.4.7) (*)		1500	350	400	400	%r	Reg	Stop
Rear fog lamp (Cl 67.4.11) (+)		1000	250	≥100 FROM STOP		%r	%r	
Parking Lamp (Cl 67.4.13) (+)		1500	350		400	%		% f
Reflex reflector Rear (Cl 67.4.8) (*)		900	350	400	400	%r		
(Non-triangular) Front (Cl 67.4.17) (+)		900	350	Central Or 400	400	fpos		
Side (Cl 67.4.12) (+)		900	350			%		
Conspicuity lamps (Cl 67.4.18) (*)		1200	250	Symmetrical		%f	%f	%f Indic

Notes:.....

IR-3

SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT

FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY) Cont.

<p>G = 'Grouped Lamps' means devices having separate illuminating surfaces and separate light sources, but a common lamp body. C = 'Combined' means devices having separate illuminating surfaces, but a common light source and common lamp body. (*) = Mandatory; (+) = If fitted. (#) = HEIGHT - To highest (Max) and lowest (Min) points on illuminating surface. Apart – Distance between innermost edges of illuminating surface. EDGE – Maximum distance from outer edge of vehicle to illuminating surface. All dimension in mm. Column (7) to (9) indicates specific lamps which may be grouped (G), combined (C) or reciprocally incorporated (R). %f = Permitted with any other front lamp.</p>	<p>R = 'Reciprocally Incorporated' means devices having separate light sources (or a single light source operating in different ways), but a common or partially common illuminating surface and a common lamp body. %r = Permitted with any other rear lamp. % = Permitted with any other lamp. Dip = Permitted with Dipped Beam. Main = Permitted with Main Beam. Fpos = Permitted with Front Position Side lamps. Park = Not permitted with Park Lamps. Park = Permitted with Park Lamps. Stop = Permitted with stop lamps. Rpos = Permitted with Rear Position Side Lamps. Reg = Permitted with Rear Registration Plate Lamp. Indic = Not permitted with Indicator Lamps.</p>	<p>COMPLIANCE Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/></p>	<p>SSR No.</p>
CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
67.3 67.3.1	VISIBILITY Are apparent surfaces of all lamps unobstructed by any parts of the vehicle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3 67.3.5	GENERAL SPECIFICATIONS Are all lamps constituting a pair symmetrical?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.9	No red light visible from the front and no white light (except reversing light) visible from the rear of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.10	Can all front and rear position lamps, the rear registration plate lamp, and the passenger car side lamps (if fitted) be only switched on and off together?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.11	Is it not possible to switch on the main-beam, dipped-beam and front and rear fog lamps without first switching on the lamps referred to in clause 67.3.10?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....

IR-3

SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT

FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY) Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
67.3.13.1	Are no lamps (other than driving, passing or front fog lamps) concealed?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.3.13.2	Is it possible to move a concealed lighting device into the position of use, without the aid of tools, in the event of a defect?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1	MAIN-BEAM HEADLAMPS Are all main beams switched off when changing over from main beam to dipped beam?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1.3.1.1	For single dipped beam application with an independent main beam. Is this main beam mounted directly above or below the dipped beam with its geometric centre situated on the longitudinal median of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1.3.1.2	For two dipped beam applications are the main beam lamps mounted no closer to the outside edge of the vehicle than the outer edge of the dipped beam headlamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.1.10	Circuit closed tell-tale colour blue and non-flashing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.2.9.1	DIPPED – BEAM HEADLAMPS	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.2.10	Control within easy reach of driver? If operational tell-tale fitted, is it green and non-flashing?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.2.3.1.1	For single lamp applications, is this lamp mounted with its geometric centre situated on the longitudinal median of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.3.1.1	DIRECTION INDICATOR LAMPS FOR LB1, LE1 (1) Front indicators at least 300 mm apart?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Front indicators further apart than the outside surfaces of the headlamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Front indicator lamps at least 100 mm from the headlamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(4) Rear indicators not more than 400mm from the extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.3.1.2	FOR LB2, LE2 (1) Front indicators not more than 400mm from the extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	67.4.3.3.3.1 (2) Rear indicators the distance between the two illuminating surfaces at least 240mm apart?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(3) Rear indicators within 300 mm of the rear of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.3.3.2	Front indicators within 1,800 mm of the front surface of the vehicle? (2,500 mm if necessary to comply with visibility requirements).	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY) Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
67.4.3.9	ALL VEHICLES Independent switch and flash in phase?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.10	(1) Is a visible tell-tale' fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2) Tell-tale behaviour on turn signal malfunction?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(A) - Marked frequency change, (B) - Continuously on, or (C) – Continuously off (Indicate A, B, C,)?	<input type="checkbox"/>	
67.4.3.11.1.1.	For DC supply indicators flash 60 to 120 times per minute?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.11.3.1	For AC supply, indicators flash 45-120 times per minute?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.11.1.3	Lights up within 1 second and extinguishes within 1.5 seconds?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.3.11.4	If one lamp fails(other than due to a short-circuit)do other lamps flash when actuated?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.4.9	STOP LAMP Lighted with any service brake application?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	If fitted, is tell-tale non-flashing operational type?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.5	REAR REGISTRATION PLATE LAMP Illuminates the registration plate area?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.5	FRONT POSITION LAMPS For LB1, LE1 One or Two lamps fitted in Dipped Beam headlamp? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.6	For LB2, LE2	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.6.1.1	Two lamps mounted with their centres symmetrical about the longitudinal medium plane of the vehicle?		
67.4.6.1.2	Not further than 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.6.3.1.2	Instrument lights as tell-tail? If NO	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.3	If No, is a non-flashing green tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.1.1	REAR POSITION LAMP (RPL) For LB1, LE1 Distance between illuminating surface at least 400mm, and within 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.1.1	For LB2, LE2	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.3.1.2	One lamp fitted on the longitudinal medium plane of the vehicle?		
67.4.7.3.1.1	Instrument light as tell-tale?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.7.10	If No, is a non-flashing green tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY) Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
67.4.8.3.1.2	REAR REFLEX REFLECTOR (NON-TRIANGULAR) For LB1, LE1 Distance between illuminating surface at least 400mm, and within 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.8.3.1.2	For LB2, LE2 One reflector fitted on the longitudinal medium plane of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.8.3.1.1	HAZARD WARNING LAMP All direction indicator lamps flash in phase?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.1	Independent switch?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.2	Flashing tell-tale fitted?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.3	Can Hazard Warning be activated with engine ignition in the off position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.9.4.1	FRONT FOG LAMPS (OPTIONAL) For LB1, LE1 Lamp centre of reference on the medium longitudinal plane or not more than 250mm from the medium longitudinal plane of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.10.3.1.1	For LB2, LE2 Lamps not more than 400mm from extreme outer edge of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.10.3.1.2	REAR FOG LAMPS (OPTIONAL) If only one lamp fitted is mounted either in the median longitudinal plane or to the right?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.11.3.1	The illuminating surface of the fog lamp at least 100mm from the illuminating surface of the stop lamp?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.11.3.4	(1)Can rear fog lamp operate only when dipped beam or main beam lamps and/or the front fog lamp is on?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	(2)Can rear fog lamp be extinguished independently of the front fog lamps (if fitted)?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
	Independent, non-flashing, circuit closed tell-tale fitted and operational?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.12	SIDE REFLEX REFLECTOR AMBER (OPTIONAL)	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.12.1	Are One or Two side reflectors fitted? Please circle.		
67.4.12.5	Is the reference axis of the side reflector perpendicular to the vehicle's median longitudinal plane and directed outwards?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR No 67/00 - INSTALLATION OF LIGHTS & LIGHT SIGNALLING DEVICES (FOR LB AND LE ONLY) Cont.

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
67.4.11.9	PARKING LAMP (OPTIONAL) For LB1, LE1 If rear oriented only, One or Two lamps fitted? Please circle If front and rear oriented Two or Three lamps fitted? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.2.1	For LB2, LE2 If rear oriented only One lamp fitted? If front and rear oriented Two or Three lamps fitted? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.2.2	Is illuminating surface not more than 400mm from extreme outer edge of the vehicle? If only two lamps provided are these provided on the side of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.9	Switch to permit parking lamps to be lit independently of any other lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.9	Able to operate with the ignition switch in 'OFF' position	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.13.10	If fitted, impossible to confuse tell-tale with that for the front and rear position Lamps?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.14.9	REVERSING LAMPS (IF REVERSE GEAR FITTED) Is the lamp always lit when reverse gear engaged and:	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.14.9	(1) The device controlling starting and stopping engine is in a position where engine can be operated?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.18.3.1	(2) The engine is running?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.18.11	CONSPICUITY LAMPS (OPTIONAL) Are One or Two conspicuity lamps fitted? Please circle Are they separate lamps or combined with Dipped-Beam headlamps ? Please circle	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.18.9.1	If conspicuity Lamps fitted, are they lit every time the engine is run?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.18.9.1	CORNERING LAMPS (OPTIONAL) Lighted continuously together with the corresponding direction indicator?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.19.9.2	Only lighted when the headlamp switch is in the on position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.20 67.4.20.4.3. 2	SIDE MARKER LAMPS (OPTIONAL, MANDATORY FOR VEHICLES >2.1m WIDE and > 7.5m IN LENGTH) Front lamps within the front 3 rd of the vehicle, but not forward of a plane through the rearmost point of the driver's seat in the rearmost position?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
67.4.20.4.3. 1	Are rear lamps not more than 300mm from the rear of the vehicle?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	

Notes:.....
.....
.....

IR-3

**SINGLE UNIFORM TYPE INSPECTION (SUTI) REPORT
FOR VEHICLES OF CATEGORY LA, LB, LC, LD AND LEM**

ADR 83/00 – EXTERNAL NOISE

CLAUSE No.	FEATURE	COMPLIANCE	SSR No.
B/C 4.1	MARKING REQUIREMENTS Silencing system components marked with:		
B/C 4.1.1	(1) Trade name or mark of manufacturer? Record Marking.....	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
B/C 4.1.2	(2) Trade description given by manufacturer? Record Marking..... (3) If 'E' marked, R41 or R63 Approval No	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> # #	
B/C 4.2	Markings clearly legible and appears indelible?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
B 6.1 B 6.1.1	LABELLING REQUIREMENTS (N/A to LA, LB Categories) Is the following information provided on the motorcycle in an easily accessible (not necessarily immediately visible) location? (1) The manufacturer's name? (2) The value in dB(A) for the stationary noise test? (3). The engine speed in RPM or MIN-1? Record details.dB(A) @RPM	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/> #	

	Has the RVD been checked and found satisfactory?	Y <input type="checkbox"/> N <input type="checkbox"/> NA <input type="checkbox"/>	
--	--	---	--

Inspector's Signature;

Name: Signature: Date:

Name: Signature: Date:

Notes:.....
.....
.....